



DIRECTIONS FOR USE

DECK+FENCE

Surface Preparation

Proper surface preparation is the key to maximum performance. The appearance and durability of Deck + Fence can be impaired by an unsound or poorly prepared surface. In order to be effective, this finish must be able to penetrate. It is very important that the surface be clean of all dirt, mildew, loose wood fibers and other foreign matter. Surfaces must be structurally sound. Previously finished or weathered wood surfaces must be either sanded (use 40 to 60 grit paper), chemically stripped with Timber Pro Strip & Brite, media blasted or power washed to restore the surface to new wood condition. New wood that appears shiny should be sanded (use 40 to 60 grit paper), or sand blasted to remove mill glaze. New rough-cut lumber should be power washed or media blasted to ensure a clean surface prior to stain application. New logs should be power washed, media blasted or sanded (use 40 to 80 grit paper) to ensure surface is clean and will allow stain to penetrate properly.

Precautions

Do not apply if rain or freezing temperature is likely to occur. Apply to a cool surface and when temperature is between 10C to 25C. Avoid application in direct sunlight. Protect product from freezing. Do not thin product.

Stirring

Stir the product well before commencing and occasionally during use. If the product requires more than one batch, blend them together. Before commencing the entire job, always test for appearance and color in an inconspicuous spot.

To avoid non-uniform appearance

On vertical siding/fence start at the bottom with several boards and continue all the way to the top. On horizontal siding/fence start at lowest run edge and follow through to a logical break, such as a corner, gate or post. For decks and docks, apply product liberally in the direction boards are installed. Back brush excessive Deck + fence to avoid leaving pooled or puddled material on surface. Siding/fence, deck and dock boards can be prefinished prior to installation. Prefinished boards should be saturated on all 6 sides and material allowed to dry between re-coats prior to installation.

Method of application

Apply by nylon polyester brush, spray or paint pad. Apply a generous coat and smooth out any runs, drips or puddles. When spraying, always back brush immediately after each section to assure proper penetration.

Number of Coats

Timber Pro Deck & Fence Formula is a 2-coat system. (2 pigmented coats) Allow 16 hours dry time between coats and at least 16 hours prior to heavy foot traffic. For lower lying decks or docks subject to heavy moisture exposure 1 coat is recommended.

Coverage Per Coat

Smooth wood coverage is approximately 6.1-7.4 m² per liter (250-300 sq ft/gallon). Rough wood coverage is approximately 3.1-3.5 m² per liter (125-150 sq ft/gallon). Coverage will vary depending on an age or surface porosity.

Maintenance

Due to the high wear and constant exposure of decks to the elements, an annual inspection is recommended. Maintenance coats of Deck + Fence could be required every 12-24 months on horizontal deck surfaces. Do not allow snow to accumulate on decks for any long length of time. In the case of fences: a maintenance coat of the Deck + Fence is recommended every 2-3 years or on south and west side and 3-4 years on north and east side. Depending on the amount of exposure, more frequent application may be necessary. Maintenance coat can be either pigmented or Clear Deck + Fence Formula. Prior to applying maintenance coat, wash surface with Timber Pro Clean + Brite, rinse well with clear water. Allow 24 hours of dry time before applying maintenance coat.

Clean Up

Clean Up: Clean brushes and equipment with soap and water.

THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Timber Pro Coatings Canada
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4
Tel: 604-270-4244 email: canadainfo@timberprocoatings.com

Warranty

When applied to new wood according to the label directions. If this Timber Pro product is proved to be defective after purchase Timber Pro Coatings Ltd. will furnish any necessary additional product free of charge or will refund the purchase price at the company's option. This warranty does not include labor or coat of labor. For the application of the product, this warranty gives you specific legal rights. And you may also have other rights that vary from country to country.

www.TimberProCoatings.ca
www.TimberProCoatings.com