



# DIRECTIONS FOR USE

# CLEAN+BRITE

## Surface Preparation

Remove any metal objects from the area and any leaves or debris from the surface. Wood should be dampened prior to application of the Clean & Brite. Wet down all plants and keep them wet during the cleaning process. Dilute the Clean & Brite to the proper application ratio as noted for each area. **NEW AND UNTREATED WOOD:** Mix 1 part Clean & Brite to 4 parts warm water. You may use a stronger concentration for wood that is very dirty, just rinse longer with clean water.

## Test Area

Test a small hidden area first to determine the exact dilution ratio necessary. Can be used full strength if necessary.

## Previously Stained Prior to Maintenance

Mix 1 part Clean & Brite to 6 parts water.

## Annual Cleaning

Mix 1 part Clean & Brite to 10 parts water.

## Method of application

Apply the solution with a garden pump sprayer, paint pad, brush, or roller. Avoid direct sun and temperatures above 25 °C (80 °F) or below 5 °C (40 °F). Allow the Clean & Brite to activate 15-30 minutes. Mist the surface with water to keep the solution damp if necessary. **DO NOT LET IT DRY ON THE WOOD.** Agitate with stiff brush if necessary. On previously stained wood, do not scrub hard. Thoroughly rinse the surface with water after the activation period with hose or power washer until the suds dissipate.

## Note

Process may cause grain raising or fuzzing of the surface fiber. Brush out when wet with stiff brush to remove the fuzz. Sand if desired to smooth out the surface. Allow thoroughly dry before application of finishes.

## Coverage

Approximately 7.4-9.8 m<sup>2</sup> per liter (300-400 sq ft/gallon) of concentrate approximately. This will vary on condition of wood and application

## Safety

**CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. CONTENTS HARMFUL.**

Do not mix with acids or oxidizers. Do not swallow. Do not get in eyes, on skin or clothing. Do not breathe fumes. Handle with care. Keep out of reach of children. Wear nitrile gloves and safety glasses. Use only in a well-ventilated area.

**FIRST AID TREATMENT:** Contains potassium hydroxide. If swallowed, call Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

## THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Timber Pro Coatings Canada  
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4  
Tel: 604-270-4244 email: canadainfo@timberprocoatings.com

## Warranty

When applied to new wood according to the label directions. If this Timber Pro product is proved to be defective after purchase Timber Pro Coatings Ltd. will furnish any necessary additional product free of charge or will refund the purchase price at the company's option. This warranty does not include labor or coat of labor. For the application of the product, this warranty gives you specific legal rights. And you may also have other rights that vary from country to country.

[www.TimberProCoatings.ca](http://www.TimberProCoatings.ca)  
[www.TimberProCoatings.com](http://www.TimberProCoatings.com)