



# DIRECTIONS FOR USE

## EZ PRO

### Surface Preparation

Proper surface preparation is the key to maximum performance. The appearance and durability of EZ PRO can be impaired by an unsound or poorly prepared surface. In order to be effective, this finish must be able to penetrate. It is very important that the surface be clean of all dirt, mildew, loose wood fibers and other foreign matter. Surfaces must be structurally sound. Previously finished or weathered wood surfaces must be either sanded (use 40 to 60 grit paper), chemically stripped with Timber Pro Strip & Brite, media blasted or power washed to restore the surface to new wood condition. New wood that appears shiny should be sanded (use 40 to 60 grit paper), or media blasted to remove mill glaze. New rough-cut lumber should be power washed or media blasted to ensure a clean surface prior to stain application. New logs should be power washed, media blasted or sanded (use 40 to 80 grit paper) to ensure surface is clean and will allow stain to penetrate properly.

### Precautions

Do not apply if rain or freezing temperature is likely to occur. Apply to a cool surface and when temperature is between 10C to 25C. Avoid application in direct sunlight. Do not thin product. Protect product from freezing.

### Stirring

Stir thoroughly before and occasionally during use. If the job requires more than one batch, blend them together. Before proceeding with the entire job,- test for appearance and color in an inconspicuous area.

### To avoid non-uniform appearance

On vertical siding, start at the bottom with several boards and continue all the way to the top. On horizontal siding and/or logs, start at the lowest run at edge and follow through to a logical break, such as a door, window or corner. For decks and docks, apply product liberally in the direction boards are installed. Back brush excessive EZ PRO to avoid leaving pooled or puddled material on surface. Siding, deck and dock boards can be prefinished prior to installation. Prefinished boards should be saturated on all six sides and material allowed to dry prior to installation.

### Method of application

Apply by spray, brush, roller, dip tank, or paint pad. Flood coat surface and then smooth out all runs, drips and puddles. When spraying or rolling, always backbrush immediately after each section is coated to ensure proper penetration.

### Number of Coats

For exterior surfaces: apply one saturated coat or a wet-on-wet coat. (Wet-on-wet coat has to be applied with-in 5 minutes of first coat). Apply as much product as wood will absorb but do not leave any pooling, puddling or runs. Thoroughly back brush to ensure proper dispersion and penetration into wood surface. EZ PRO is designed as a 'one-coat' stain. A second coat can be applied after the first coat has dried (two to four hours). A second coat will enhance protection and offer extended performance both vertically and horizontally.

### Coverage Per Coat

On rough-sawn wood: coverage is 3.5-5 m<sup>2</sup> per liter (150-200 sq ft per gallon). Smooth wood: coverage is 6.1-7.4 m<sup>2</sup> per liter (250-300 sq ft/gallon). Exotic woods (hardwoods): coverage is 7.4-9.8 m<sup>2</sup> per liter (300-400 sq ft /gallon). Aged porous wood: coverage is 3.5-5m<sup>2</sup> per liter (150-200 sq ft per gallon). Coverage may vary depending on the porosity of the wood.

### Maintenance

Depending upon exposure or wear, evaluate recoating needs every 1-3 years. EZ PRO can be applied on an as-needed basis as part of an ongoing maintenance program. Prior to applying the maintenance coat, wash the surface with Timber Pro Clean + Brite, rinse well with clear water. Allow 24 hours of dry time before applying the maintenance coat.

### Clean Up

Clean Up: Clean brushes and equipment with soap and water.

## THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Timber Pro Coatings Canada  
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4  
Tel: 604-270-4244 email: canadainfo@timberprocoatings.com

### Warranty

When applied to new wood according to the label directions. If this Timber Pro product is proved to be defective after purchase Timber Pro Coatings Ltd. will furnish any necessary additional product free of charge or will refund the purchase price at the company's option. This warranty does not include labor or coat of labor. For the application of the product, this warranty gives you specific legal rights. And you may also have other rights that vary from country to country.

[www.TimberProCoatings.ca](http://www.TimberProCoatings.ca)  
[www.TimberProCoatings.com](http://www.TimberProCoatings.com)