



# DIRECTIONS FOR USE

# ULTRA DF

## Surface Preparation

Proper preparation is the key to maximum performance. The appearance and durability of this product can be impaired by an unsound or poorly prepared surface. To be effective, the finish must be able to penetrate. It is very important that the surface be clear of all dirt and mildew, loose wood fibers and other foreign matter. Surfaces must be structurally sound. Previously finished wood must be stripped of old coating by; chemically stripped with Timber Pro Strip & Brite, media blasted or sanding with plate sander or random orbital sander. If chemically stripped, you must use a plate sander or random orbital sander to open the wood grain and level the surface. Use only 40 to 60 grit sandpaper. Weather wood can be washed with a pressure washer (low pressure, wide fan tip spray pattern), Timber Pro Clean + Brite, and then sanded as noted above. New wood must be washed and then sanded as noted above to remove mill glaze.

## Precautions

Do not apply if rain or freezing temperature is imminent. Do not apply in direct sunlight or to hot surfaces. Do not apply above 25 °C (80 °F). Do not thin the product. Protect from freezing. Wood must feel cool to touch or do not apply.

## Stirring

Stir the product well before commencing and occasionally during use. If the product requires more than one batch, blend them together. Before commencing the entire job, always test for appearance and colour in an inconspicuous spot.

## To avoid non-uniform appearance

On vertical siding/fence boards, start on bottom with several boards and continue all the way to the top. On horizontal siding/fence boards, start at the lowest run and follow through to a logical break such as post to post, to a corner or end of run. For decks and docks, apply in the direction the boards are installed. On all surfaces, liberally apply Ultra DF, then back brush surface to remove all puddles, pools, drips or runs.

## Method of application

Apply by nylon polyester brush, spray and back brush, or paint pad. Apply a generous coat and smooth out any runs, drips, or puddles. When spraying, always back brush immediately after each section to assure proper penetration. Deck and fence boards can be coated prior to installation on all 6 sides, this increases performance and provides additional protection to wood.

## Number of Coats

Apply 2 coats of Timber Pro Ultra DF Formula allow 16 hours dry between coats and at least 16 hours prior to heavy foot traffic. For lower lying decks or decks subject to heavy moisture exposure 1 coat is recommended.

## Coverage Per Coat

Smooth wood coverage is approximately 6.1-7.4 m<sup>2</sup> per liter (250-300 sq ft/gallon). Rough wood coverage is approximately 3.1-3.5 m<sup>2</sup> per liter (125-150 sq ft/gallon). Coverage will vary depending on an age or surface porosity.

## Maintenance

Due to the high wear and constant exposure of decks to the elements this application may require more frequent application. An annual inspection is recommended and application of Timber Pro Ultra DF Formula every 12-18 months. Do not allow snow to accumulate on decks for any long length of time. In the case of fences, a maintenance of coat of the Timber Pro Ultra DF Formula is recommended every 2-3 years on south and west side and 3-4 years on north and east side.

## Clean Up

Clean Up: Clean brushes and equipment with soap and water.

## THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Timber Pro Coatings Canada  
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4  
Tel: 604-270-4244 email: canadainfo@timberprocoatings.com

## Warranty

When applied to new wood according to the label directions. If this Timber Pro product is proved to be defective after purchase Timber Pro Coatings Ltd. will furnish any necessary additional product free of charge or will refund the purchase price at the company's option. This warranty does not include labor or coat of labor. For the application of the product, this warranty gives you specific legal rights. And you may also have other rights that vary from country to country.

[www.TimberProCoatings.ca](http://www.TimberProCoatings.ca)  
[www.TimberProCoatings.com](http://www.TimberProCoatings.com)