



DIRECTIONS FOR USE YARD TREATMENT

Surface Preparation

The surface must be relatively free from dirt, discolouration, and loose fibres. The cambium layer must be removed to allow the Yard Treatment to penetrate into the logs. Protect, cover, or mask all nearby surfaces not being treated.

Precautions

Do not apply if rain or freezing temperatures are likely to occur. Do not allow Yard Treatment to freeze.

Stirring

Stir contents well prior to use and again during use periodically.

Method of application

Saturate the wood using a low-pressure sprayer. Apply the product heavily either on a low-pressure garden-type sprayer or HVLP sprayer. Higher-pressure sprayers tend to atomize the product resulting in loss of product. Allow the product to absorb, and then brush out any runs or drips.

Number of Coats

Apply one saturated coat or use a "wet on wet" application method to ensure total saturation of wood surface when using Yard Treatment formula. Be sure to back brush any runs, drips or pools of Yard Treatment.

Coverage Per Coat

Yard Treatment covers approximately 250-350 sq. ft./gallon depending on wood surface porosity.

Drying Time

Yard Treatment will dry in 6 to 12 hours time depending on humidity and ambient air temperature.

Clean Up

Clean up overspray, drips and splashes immediately with water. Clean all tools & application equipment with soap & water.

THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Timber Pro Coatings Canada
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4
Tel: 604-270-4244 email: mark@timberprocoatings.ca

Warranty

When applied to new wood according to the label directions. If this Timber Pro product is proved to be defective after purchase Timber Pro Coatings Ltd. will furnish any necessary additional product free of charge or will refund the purchase price at the company's option. This warranty does not include labor or coat of labor. For the application of the product, this warranty gives you specific legal rights. And you may also have other rights that vary from country to country.

www.TimberProCoatings.ca