



Ultra DF Formula

Technical Data Sheet

Revised July 25, 2019

Description

Timber Pro Ultra DF Formula is a premium exterior wood finish formulated with a unique blend of natural oils and resins. **Ultra DF Formula** utilizes a unique formula which gives ultimate penetration into the wood. **Ultra DF Formula** not only accentuates the natural beauty of the wood but it also provides you protection against the damaging UV rays from the sun and destructive effects of the elements.

Where to Use

Timber Pro Ultra DF Formula can be used on all new and reconditioned exterior wood. **Ultra DF Formula** can be used on all wood species such as cedar, fir, pine, cypress, redwood, spruce and pressure treated wood. The following are areas of use for **Ultra DF Formula**.

- Decks
- Fences

RESTRICTIONS

- Do not thin
- Do not apply over previously coated surfaces

Features and Benefits

- Low V.O.C.
- Excellent UV protection
- Excellent weathering properties
- Large color range
- Easy soap and water cleanup

Colour Range and Packaging

Colour : Clear

(TR) Transparent series	36 colours available
(ST) Semi Transparent series	18 colours available
(SS) Semi Solid series	15 colours available
(IS) Interior Stain series	10 colours available
(XP) XP Stain series	8 colours available

Packaging: 1 US gallon
5 US gallon Pail

Timber Pro Coatings Ltd

140-12051 Horseshoe Way, Richmond, BC V7A 4V4
Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244
Email: canadainfo@timberprocoatings.com



Ultra DF Formula

Technical Data Sheet

Revised July 25, 2019

Properties

Viscosity -	20-23 secs Zahn cup #2
Gloss Level -	Matte 10-20 GU @ 60 degree
Solids by Weight -	17.8 % +/- 1%
Solids by Volume -	18.1% +/- 1%
V.O.C. -	86 g/l minus water
Weight per gallon-	8.49 lbs/gal.
Specific Gravity-	1.02
Dry Time -	2-4 hrs touch dry 16hrs through dry for heavy traffic

Note: dry times will be extended at low temperatures and high humidity

Shelf Life

Approximately two years in an unopened container

KEEP FROM FREEZING

Coverage

Smooth Wood: 300-400 square feet per gallon

Rough Wood : 150 – 200 square feet per gallon

Hardwoods: 400-450 square feet per gallon

Note : Coverage will vary with the porosity of the wood

Application

Use a spray applicator, nylon polyester brush or 25ml or 30ml roller and back-brush

Clean Up

Timber Pro Coatings Ltd

140-12051 Horseshoe Way, Richmond, BC V7A 4V4

Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244

Email: canadainfo@timberprocoatings.com



Ultra DF Formula

Technical Data Sheet

Revised July 25, 2019

With soap/mild detergent & water

Product Disclaimer

The technical information and suggestions for use herein are based on **Timber Pro Coatings Ltd** research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since **Timber Pro Coatings Ltd** has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.