


INTERIOR STAIN

INTERIOR STAIN



FEATURES:

- **EXCELLENT UV PROTECTION:** Unique UV absorbers and enhanced micronized pigments protect wood.
- **BREATHABLE FINISH:** Interior Stain is breathable formula that reduces moisture build up in wood and stabilizes wood to reduce warping and checking.
- **LOW VOC FORMULA:** Interior Stain is not harmful to the environment.
- **LOW ODOUR:** Interior Stain formula is a low odour product making it idea for interior use.
- **EASY TO APPLY:** Interior Stain can easily be applied by brush, pad or sprayed and back brushed.
- **EASY TO MAINTAIN:** The unique formula does not peel, flake, or blister.
- **EASY TO CLEAN UP:** Soap and water clean-up.

INTERIOR STAIN

Protects + Beautifies

- Interior of Log Homes, Timber Frame and Post & Beam structures
- Floors
- Cabinets and Furniture
- All Interior wood Trim, Walls, Ceilings, Stairs, and Railings

Timber Pro Interior Stain is a waterborne Alkyd wood stain designed to enhance and beautify the colour of your interior wood projects. The low odour and low VOC make this an ideal product for all interior wood finishing.

Interior Stain is a versatile wood stain providing a broad colour palette. Interior Stain can be used on its own as an oil finish or it can be used in combination with Timber Pro Crystal Urethane or XP. When Crystal Urethane or XP are used in combination with Interior Stain, they provide a durable topcoat that enhances Interior Stain wood tones and protects your interior wood.

Crystal Urethane and XP are available in a variety of sheen levels.



DEALER STAMP

604.270.4244
timberprocoatings.ca



INTERIOR STAIN

Protects + Beautifies

Where to Use

Timber Pro Interior Stain can be used indoors on all new and reconditioned wood. Interior Stain can be used on wood species such as cedar, fir, pine, cypress, redwood, hard and soft woods. LOG+SIDING can be used for:

- Log Homes and Timber Frame • Cabinets and Furniture
- Trim • Doors/Windows/Stairs
- Post and beams • Floors

RESTRICTIONS

- Do not apply the product to an unprepared surface
- Do not thin the product
- Do not apply on surfaces hot to the touch
- Do not apply in direct sunlight or temperatures below 10C (50F) and above 25C (80F)
- Do not apply over previously coated surfaces

Application

- Do a colour test before proceeding with the entire job. Apply one or two colour coats depending on the desired outcome. Allow each coat to dry before proceeding with the next coat.
- Check moisture content of the wood. Apply coating when the surface moisture is less than 21%.
- Stir the product thoroughly before and occasionally during use.
- Best results are with a quality nylon/polyester brush. Airless sprayer application is acceptable but must be immediately back brushed.
- Generously coat the surface and all exposed end grain. Apply as liberally as possible without runs. Do not try to stretch the coverage. Apply in the direction of the grain. On rough-sawn surfaces, thoroughly saturate and back brush to soak as much product as possible into the wood. If spraying, spray until product runs slightly, then immediately back brush. Avoid lap marks by starting at one end of a given surface and while maintaining a wet edge, follow through to the opposite end of the surface area. It is extremely important to allow each coat to dry before proceeding with the next coat or applying a clear top coat such as XP or Crystal Urethane.

Clean Up

Wash with soap/mild detergent and water

Coverage

Smooth wood: 250-300 square feet per gallon.
Rough wood: 150-200 square feet per gallon.
Hardwoods: 300-350 square feet per gallon.
Note: Coverage will vary with the porosity of the wood.

THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Log+Siding
Ultra DF
Roof Treatment
Yard Treatment

Ultra LS
Crystal Urethane
Strip+Brite
EZ PRO

Deck+Fence
Timber Seal
Interior Stain Formula
Base Coat

XP
Clean+Brite

Timber Pro Coatings Canada
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4
Tel: 604-270-4244

www.TimberProCoatings.ca