



# DIRECTIONS FOR USE

## STRIP+BRITE

### Surface Preparation

Wet down all plants heavily prior to and during application. Remove all metal objects, which may tarnish. Dampen the wood surface prior to application of the Strip & Brite.

### Test Area

Depending on the condition of the wood surface the STRIP & BRITE should either be used full strength or it can be diluted 1:1 with water for less severe wood surface conditions. Test both on a small section of most discolored area. Follow application step 1 & 2 and then let dry before determine effectiveness.

### Application

#### Step 1

Apply the Strip & Brite solution to water dampened wood using a low-pressure sprayer or roller. Avoid direct sunlight and temperatures above 25°C (80 °F) or below 5° C (40 °F). Allow to activate for 30 minutes, or up to 4 hours for heavily built up or previously applied stain or finish. **DO NOT LET THE STRIP & BRITE DRY ON WOOD.** Reapply or mist with water if drying starts to occur. Work in sections that are manageable. Agitate with stiff brush or broom if necessary. Rinse with plenty of water either with hose or power washer. Let standing water dissipate and proceed to STEP 2.

#### Step 2 (NEUTRALIZER - BRIGHTENER)

Mix neutralizer crystals according to the instructions on the package. Apply after STEP 1 by low-pressure sprayer to the wood surface. The darkened surface from STEP 1 will lighten which is the indicator that the surface is properly neutralized and the wood has been restored to the proper pH. Once neutralized, rinse the surface with plenty of clean water. **DO NOT SKIP STEP 2.**

Prior to application of any coating, allow the surface to properly dry.

### Coverage

Depends on concentration level or what is being removed. Generally, 2.5-7.4 m<sup>2</sup> per liter (100-300 sq ft/gallon).

### Note

Process may cause wood grain to raise and fuzz up. When step 2 is completed and rinsed, agitate with a clean stiff brush while still wet to remove fuzz. Sand only if desired.

### Safety

**CAUSES BURNS. DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS. CONTENTS HARMFUL.**

Do not mix with acids or oxidizers. Do not swallow. Do not get in eyes, on skin or clothing. Do not breathe fumes. Handle with care. Keep out of reach of children. Wear nitrile gloves and safety glasses. Use only in a well-ventilated area.

**FIRST AID TREATMENT:** Contains potassium hydroxide. If swallowed, call Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 20 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

## THE COMPLETE LINE OF TIMBER PRO PRODUCTS

Timber Pro Coatings Canada  
Unit 140, 12051 Horseshoe Way, Richmond BC, V7A 4V4  
Tel: 604-270-4244 email: canadainfo@timberprocoatings.com

### Warranty

When applied to new wood according to the label directions. If this Timber Pro product is proved to be defective after purchase Timber Pro Coatings Ltd. will furnish any necessary additional product free of charge or will refund the purchase price at the company's option. This warranty does not include labor or coat of labor. For the application of the product, this warranty gives you specific legal rights. And you may also have other rights that vary from country to country.

[www.TimberProCoatings.com](http://www.TimberProCoatings.com)