



Interior Stain Formula

Technical Data Sheet

March 2013

IS-Series

TR-Series

ST-Series

SS-Series

Description

The Timber Pro Interior Stain Formula is a deeply penetrating natural oil wood stain specially formulated to enhance and beautify the color of your interior wood. The Interior Stain Formula provides a low VOC and a low odour staining alternative for your interior wood.

Where to Use

Interior Stain formula is a versatile wood stain providing a broad colour palette achieve the desired colors to match your interior décor.

Used in combination with Timber Pro Crystal urethane this provides a durable topcoat to protect your interior wood projects.

- All interior wood walls, doors
- All interior wood trim work
- Interior wood floors
- Interior wood cupboards and countertops

RESTRICTIONS

- Do not thin
- Do not apply over previously coated surfaces

Features and Benefits

- Broad Colour Range of 56 colours to match all your interior needs.
- Low odour making ideal for interior application.
- 3 Sheen levels: Used in combination with Timber Pro Crystal Urethane a satin, semi-gloss and gloss finish can be achieved to match and accent your interior decor
- Easy to apply with spray, nylon polyester brush, or paint pad
- Low VOC formula is better for the environment.
- Easy soap and water cleanup

Interior Stain Formula

Technical Data Sheet

March 2013

IS -Series

TR-Series

ST-Series

SS-Series

Color Range and Packaging

Color :	Clear (IS series) Interior	10 colors
	(TR series) Transparent	24 colors available
	(ST series) Semi Transparent	18 colors available
	(SS series) Semi Solid	14 colors available

Packaging: 1 US Quart 1 US Gallon

Properties

Viscosity -	20-21 secs Zahn cup #2
Gloss Level -	55 + GU @ 60 degree
Solids by Weight -	20.0 % +/- 1%
Solids by Volume -	20.5% +/- 1%
V.O.C. -	108 g/l minus water
Weight per gallon-	8.42 lbs./Gal.
Specific Gravity-	1.01
Dry Time -	2-4 touch dry 16 hours through dry Note dry times will be extended at low temperatures and high humidity

Shelf Life

Approximately two years in an unopened container

KEEP FROM FREEZING

Coverage

Smooth Wood: 250-300 square feet per gallon

Rough Wood : 150 – 200 square feet per gallon

Hardwoods: 300-400 square feet per gallon

Note : Coverage will vary with the porosity of the wood

Interior Stain Formula

Technical Data Sheet

March 2013

IS-Series

TR-Series

ST-Series

SS-Series

Application

Use a spray applicator , Roller or nylon polyester brush, paint pad

Clean Up

With soap and mild detergent

Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

Timber Pro Coatings Ltd

#140-12051 Horseshoe Way, Richmond, BC V7A 4V4

Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244

info@timberprocoatings.ca

timberprocoatings.ca



MATERIAL SAFETY DATA SHEET

Date of issue : March 6 2013

Revision Date: Nov 27, 2018

SECTION 01: PRODUCT & COMPANY IDENTIFICATION

Manufactured by: Timber Pro Coatings Ltd
140 -12051 Horseshoe Way
Richmond, B.C.
V7A 4V4
(604) 270-4244

Product Name: Interior Stain Formula

Product Type : Natural Oil Wood Finish
UN Number : Not applicable
Product Class : Protective / decorative coating
C.A.S. Number : Mixture

SECTION 02: HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Maximum Content</u>	<u>Exposure LD50s and LC 50s Route and species</u>
Dipropylene glycol methyl ether	34590-94-8	1-2%	Oral LD50 Rat : 5400uL/Kg Dermal LD50 Rabbit 10ml/kg Inhalation LC50 Rat ; >500ppm/7hrs(>661ppm/4hrs)
Propylene Glycol	57-55-6	1-2%	Oral LD50 (Rat) 20000mg/Kg Dermal(Rabbit) 20800mg/Kg

SECTION 03: PHYSICAL DATA

Physical State Liquid
Appearance Viscous opaque cream coloured liquid
Odour Negligible
Evaporation Rate Equals water
Boiling Point 100°C (212°F)
Freezing Point 0°C (32°F)
Specific Gravity 1.01
Volatile %, max 79 % by weight
VOC, Max 109 grams per litre minus water

Interior Stain Formula MSDS

CONTINUED



SECTION 04: FIRE AND EXPLOSION HAZARD DATA

Flammability Class: N/A **Flash Point:** N/A **LEL:** N/A

WHMIS Class Non-combustible liquid

Extinguishing Media:

Foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool.

Special Firefighting Procedures:

Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus.

Unusual Fire & Explosion Hazards:

Closed containers may rupture when exposed to extreme heat.

Air oxidation of this product may cause it to spontaneously ignite. **To avoid spontaneous combustion, soak soiled rags, spray booth filters and over spray wastes in a water-filled container.**

SECTION 05: HEALTH HAZARD DATA

Skin Contact: Repeated exposure and washing may irritate the skin.

Inhalation: Excessive exposure to vapours or spray mists may cause irritation of the respiratory tract.

Eye Contact: May cause upper respiratory irritation.

Carcinogenicity: This material does not contain 0.1% or more of any substance which is listed as a carcinogen by NTP, TARC or OSHA.

First Aid: Skin: Wash with soap and water immediately.

Eyes: Flush with large quantities of water for 15 minutes and seek medical attention.

Ingestion: If ingested get medical attention immediately.

SECTION 06: REACTIVITY DATA

Chemical Stability: Stable

Incompatibility: Strong oxidizing agents

Reactivity Conditions: Not reactive

Haz. Decomp Products: Carbon Dioxide, Carbon Monoxide

SECTION 07: SPILL OR LEAK PROCEDURES

Leaks or spills: Wear protective equipment during cleanup. Ventilate area. Keep spectators away. Floor may be slippery. Contain spill with inert material or absorbent such as sawdust vermiculite or sand. Do not allow material to enter drain or waterways.

Waste Disposal: Allow the absorbed material to dry and landfill the solids in accordance with current federal, state, provincial and local regulations.



SECTION 08: SPECIAL PROTECTION INFORMATION

Clothing: Long sleeved cover-alls, rubber gloves, goggles and safety shoes are recommended.
Ventilation: General ventilation is required during normal use. Local ventilation may be required during certain operations, which generate fumes or spray mists.
Respiratory: A canister type respirator may be necessary if spray mists or fumes are generated. A NIOSH approved organic vapour mask with a dust/mist pre-filter is recommended.

SECTION 09: SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing:
Avoid prolonged or repeated inhalation of heated vapours or spray mists. Keep away from heat or open flame. Avoid all skin contact.
Other Precautions: None known.

SECTION 10: SUPPLEMENTAL INFORMATION

Regulatory Information

TDG / DOT Not regulated
DSL / TSCA All raw materials listed
HMIS Rating: Health = 2 Fire = 0 Reactivity = 0

SARA & WHMIS Classification: This material is not considered as a hazardous substance as defined by SARA Title 111 regulations (40 CFR 372)

SARA SECTION 313 LISTED INGREDIENTS: This material does not contain any substance which is subject to the reporting requirements of 40 CFR 372

CANADIAN WHMIS CLASSIFICATION: D1A, D1B, D2B

Storage & Shipping: Keep from freezing.
TDG Class: Not Regulated
DOT: Not Regulated

Disclaimer : While Timber Pro Coatings believes the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Timber Pro Coatings assumes legal liability. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with Federal, State and Provincial and local laws and regulations.

PROCHAINEMENT