



# Roof Treatment

## Technical Data Sheet

March 2013

### Description

Timber Pro Roof Treatment is a premium exterior wood finish formulated with a unique blend of natural oils and resins. The Roof Treatment not only accentuates the natural beauty of the wood but it also provides unsurpassed protection against the damaging UV rays from the sun and destructive effects of the elements especially associated with roof shakes.

### Where to Use

Timber Pro Roof Treatment can be used on all new and reconditioned wood roof shakes. Timber Pro UV can be used on all wood species such as cedar and redwood. The following are areas of use for the Timber Pro Roof treatment.

- Roof shakes
- Roof Shingles

### RESTRICTIONS

- Do not thin
- Do not apply over previously coated surfaces

### Features and Benefits

- Can be used in interior and exterior wood surfaces
- Low V.O.C.
- Excellent UV protection
- Excellent weathering properties
- Large color range
- Easy soap and water cleanup



# Roof Treatment

## Technical Data Sheet

March 2013

### Color Range and Packaging

<b>Color :</b>	(TR series ) Transparent	24 colors available
	(ST series ) Semi Transparent	18 colors available
	(SS series ) Semi Solid	14 colors available

Packaging: 5 US Gallon Pail

### Properties

<b>Viscosity -</b>	20-23 secs Zahn cup #2
<b>Gloss Level -</b>	Satin 25 - 35 GU @ 60 degree
<b>Solids by Weight -</b>	23.2 % +/- 1%
<b>Solids by Volume -</b>	22.5% +/- 1%
<b>V.O.C. -</b>	94 g/l minus water
<b>Weight per gallon-</b>	8.42 lbs./Gal.
<b>Specific Gravity-</b>	1.01
<b>Dry Time -</b>	2-4 touch dry 16 hours through dry Note dry times will be extended at low temperatures and high humidity

### Shelf Life

Approximately two years in an unopened container

**KEEP FROM FREEZING**

### Coverage

Rough Wood : 100-150 square feet per gallon

Note : Coverage will vary with the porosity of the wood



# Roof Treatment

## Technical Data Sheet

March 2013

### Application

Use a spray applicator , nylon polyester brush

### Clean Up

With soap and mild detergent

### Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

#### **Timber Pro Coatings Ltd**

#140-12051 Horseshoe Way, Richmond, BC V7A 4V4

Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244

Email: [canadainfo@timberprocoatings.com](mailto:canadainfo@timberprocoatings.com)



# MATERIAL SAFETY DATA SHEET

Date of issue : March 6 2013

Revision Date: Nov 27, 2018

## SECTION 01: PRODUCT & COMPANY IDENTIFICATION

Manufactured by: Timber Pro Coatings Ltd  
140 -12051 Horseshoe Way  
Richmond, B.C.  
V7A 4V4  
(604) 270-4244

**Product Name:** Roof Treatment

**Product Type :** Natural Oil Woodfinish  
**UN Number :** Not applicable  
**Product Class :** Protective / decorative coating  
**C.A.S. Number :** Mixture

## SECTION 02: HAZARDOUS INGREDIENTS

<u>Ingredients</u>	<u>CAS #</u>	<u>Maximum Content</u>	<u>Exposure LD50s and LC 50s Route and species</u>
Dipropylene glycol methyl ether	34590-94-8	1-2%	Oral LD50 Rat : 5400uL/Kg Dermal LD50 Rabbit 10ml/kg Inhalation LC50 Rat ; >500ppm/7hrs(>661ppm/4hrs)
Propylene Glycol	57-55-6	1-2%	Oral LD50 (Rat) 20000mg/Kg Dermal(Rabbit) 20800mg/Kg

## SECTION 03: PHYSICAL DATA

**Physical State** Liquid  
**Appearance** Viscous opaque cream coloured liquid  
**Odor** Slight ammonia odour  
**Evaporation Rate** Equals water  
**Boiling Point** 100°C (212°F)  
**Freezing Point** 0°C (32°F)  
**Specific Gravity** 1.01  
**Volatile %, max** 80.0 % by weight  
**VOC, Max** 93.6 grams per litre minus water

Roof Treatment MSDS

CONTINUED

**SECTION 04: FIRE AND EXPLOSION HAZARD DATA**

**Flammability Class:** N/A                      **Flash Point:** N/A                      **LEL:** N/A

**WHMIS Class**                      Non-combustible liquid

**Extinguishing Media:**

Foam, dry chemical, carbon dioxide or any Class B extinguishing agent. Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool.

**Special Firefighting Procedures:**

Firefighters and others exposed to vapors or products of combustion should wear self-contained breathing apparatus.

**Unusual Fire & Explosion Hazards:**

Closed containers may rupture when exposed to extreme heat.

Air oxidation of this product may cause it to spontaneously ignite. **To avoid spontaneous combustion, soak soiled rags, spray booth filters and over spray wastes in a water-filled container.**

**SECTION 05: HEALTH HAZARD DATA**

**Skin Contact:** Repeated exposure and washing may irritate the skin.

**Inhalation:** Excessive exposure to vapours or spray mists may cause irritation of the respiratory tract.

**Eye Contact:** May cause upper respiratory irritation.

**Carcinogenicity:** This material does not contain 0.1% or more of any substance which is listed as a carcinogen by NTP, TARC or OSHA.

**First Aid:** Skin: Wash with soap and water immediately.

Eyes: Flush with large quantities of water for 15 minutes and seek medical attention.

Ingestion: If ingested get medical attention immediately.

**SECTION 06: REACTIVITY DATA**

**Chemical Stability:** Stable

**Incompatibility:** Strong oxidizing agents

**Reactivity Conditions:** Not reactive

**Haz. Decomp Products:** Carbon Dioxide, Carbon Monoxide

**SECTION 07: SPILL OR LEAK PROCEDURES**

**Leaks or spills:** Wear protective equipment during cleanup. Ventilate area. Keep spectators away. Floor may be slippery. Contain spill with inert material or absorbent such as sawdust vermiculite or sand. Do not allow material to enter drain or waterways.

**Waste Disposal:** Allow the absorbed material to dry and landfill the solids in accordance with current federal, state, provincial and local regulations.



**SECTION 08: SPECIAL PROTECTION INFORMATION**

**Clothing:** Long sleeved cover-alls, rubber gloves, goggles and safety shoes are recommended.  
**Ventilation:** General ventilation is required during normal use. Local ventilation may be required during certain operations, which generate fumes or spray mists.  
**Respiratory:** A canister type respirator may be necessary if spray mists or fumes are generated. A NIOSH approved organic vapour mask with a dust/mist pre-filter is recommended.

**SECTION 09: SPECIAL PRECAUTIONS**

**Precautions to be taken in handling and storing:**  
Avoid prolonged or repeated inhalation of heated vapours or spray mists. Keep away from heat or open flame. Avoid all skin contact.  
**Other Precautions: None known.**

**SECTION 10: SUPPLEMENTAL INFORMATION**

**Regulatory Information**

**TDG / DOT** Not regulated  
**DSL / TSCA** All raw materials listed  
**HMIS Rating:** Health = 2 Fire = 0 Reactivity = 0

**SARA & WHMIS Classification:** This material is not considered as a hazardous substance as defined by SARA Title 111 regulations (40 CFR 372 )

**SARA SECTION 313 LISTED INGREDIENTS:** This material does not contain any substance which is subject to the reporting requirements of 40 CFR 372

**CANADIAN WHMIS CLASSIFICATION:** D1A, D1B, D2B

**Storage & Shipping:** Keep from freezing.  
TDG Class: Not Regulated  
DOT: Not Regulated

**Disclaimer :** While Timber Pro Coatings believes the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which Timber Pro Coatings assumes legal liability. They are offered solely for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with Federal, State and Provincial and local laws and regulations.

**PROCHAINEMENT**